

VIKING NEW PRODUCT ANNOUNCEMENT

COMMUNICATION & SECURITY SOLUTIONS

SR-IP
SIP Loud Ringer/
Visual Ring Indicator

July 29, 2015

SIP Loud Ringer with Visual Ring Indication and Remote Strobe Light Control

The **SR-IP** is a SIP compliant PoE powered audio device for providing loud ring and visual ring indication for SIP VoIP phone systems. When registered with a SIP server, the **SR-IP** will ring in one of 4 programmable ring patterns and flash a bright red LED upon ring detection. During ring detection the units internal relay contacts will also activate providing a trigger for a Viking Model **SL-2** Strobe light or **LPL-1** visual ring indicator.

Equipped with a high efficiency Class D power amplifier and high quality loud speaker, the **SR-IP** is typically over 10 times louder than a telephone speaker. The advanced features of the **SR-IP** include programmable Automatic Gain Control (AGC) technology which automatically increases loud ring volume to compensate for background ambient noise. The AGC



feature is ideal for variable noise environments (offices, classrooms, restaurants, etc.), and ensures that ringing is always heard but not unnecessarily loud.

⚠ Installation requires the assistance of a Network Administrator / IT Technician.

Features

- Programming software included
- 2 Amp relay contacts for Viking LPL-1 or SL-2 strobe light control
- Bright red visual ring indicator LED
- SIP compliant
- PoE powered (class 2, <6.5 watts)
- Automatic Gain Control (AGC) to automatically increase ring volume to compensate for ambient noise
- Network downloadable firmware
- Surface mounts to a single gang or 4" x 4" electrical box or directly to a wall or post
- Remotely programmable
- Extended temperature range (-40°F to 140°F)
- Remotely adjust ringer volume
- Four programmable ring cadences: normal (2 sec ON / 4 sec OFF), double, short-short-long, short-long-short
- Optional LPL-1 Remote Visual Ring Indicator (DOD# 640)
- Optional SL-2 or BLK-4-EWP strobe light kit available (DOD# 242/653)

Applications

- Loud Ringer for noisy or variable noise environments (offices, classrooms, factories)
- Visual Ring Indicator for quiet areas (Hospitals, Church, Theater)

www.vikingelectronics.com
Information: (715) 386-8861

Ordering Information

Model: SR-IP
UPC Code: 615 687 226 423
Case Quantity: 6
Document on Demand: 577
Shipping Weight: 1.5 lbs (0.75 kg)